

Verde-Lawn Hydro™

**Coarse
SGN 220**

**Quick Acting Calcitic Limestone
plus Soil Moisture Retention**

GUARANTEED ANALYSIS

Calcium (Ca)	37.0%
Magnesium (Mg)	0.6%
Calcium Carbonate (CaCO ₃)	95.0%
Magnesium Carbonate (MgCO ₃)	2.0%
Calcium Carbonate Equivalent (CCE)	91.0%
Effective Neutralizing Value (ENV)	90.0%
Effective Neutralizing Power (ENP)	1776 Pounds ENP/Ton
Total Neutralizing Power (TNP)	91.0%
Relative Neutralizing Value (RNV)	90.0%
Moisture Content Does Not Exceed	1.0%
OK ECCE	89.9%
Oregon Lime Score	90.0
Florida: 1,978 lbs of product equal to one ton of standard liming material	

Derived from Calcium Carbonate

ALSO CONTAINS NON-PLANT FOOD INGREDIENTS:

- 1.00% Polyhydroxycarboxylic Acid (from plant extracts)
- 2.00% Non-ionic Polyol

Polyhydroxycarboxylic acid as a complexing agent.
2 quarts of non-ionic polyol per 200 pounds.

SIEVE ANALYSIS PRIOR TO PRILLING

Percent Passing 4 Mesh Sieve	100%
Percent Passing 8 Mesh Sieve	100%
Percent Passing 10 Mesh Sieve	100%
Percent Passing 20 Mesh Sieve	100%
Percent Passing 40 Mesh Sieve	100%
Percent Passing 50 Mesh Sieve	100%
Percent Passing 60 Mesh Sieve	98%
Percent Passing 100 Mesh Sieve	95%
Percent Passing 200 Mesh Sieve	90%

Meets WV Fineness classification for pulverized

F1435

CONDITIONS OF SALE

Seller warrants that products will be labeled as required under state and federal laws and that they conform to the label description. Any non-conformance must be reported in writing to Seller within Thirty (30) days after purchase as a prerequisite to maintaining any claim against Seller. Buyer agrees to inspect all products purchased immediately upon delivery. The Seller's liability under this warranty is limited in amount to the purchase price of the product. This warranty is in lieu of all other warranties, expressed or implied, including warranties of merchantability and fitness for a particular purpose. There are no warranties which extend beyond this statement.

LOT NO:

NET WGT. 50 LBS. (22.68 KGS.)

APPLICATION RECOMMENDATIONS

To maintain optimum pH and improve soil moisture retention, apply **Verde-Lawn Hydro** at 5 pounds per 1,000 ft² or 220 pounds per acre (250 kg/ha) at least twice per growing season, or as needed. Soil test recommendations should be used to determine liming needs.

To adjust pH, apply **Verde-Lawn Hydro** at 10 pounds per 1,000 ft² or 435 pounds per acre (500 kg/ha), or as needed. In most soils this will raise the soil pH up to one full point (5.0-6.0). Retest, and if needed, reapply at this rate.

INSTRUCCIONES DE USO

Para mantener el pH y mejorar la humedad del suelo, aplique **Verde-Lawn Hydro**. 5 libras para cada 1.000 pie² o 220 libras para cada acre (250 kg/ha) por lo menos dos veces durante la periodo de crecimiento o cuando sea necesario. Utilice las recomendaciones de la prueba del suelo de determinar la cantidad de cal necesaria.

Para corregir el pH, aplique **Verde-Lawn Hydro**. 10 libras para cada 1.000 pie² o 435 libras para cada acre (500 kg/ha) o cuando sea necesario. En la mayoría de los suelos, esto aumentará el pH del suelo por un punto (5,0 a 6,0). Prueba una vez más el suelo. Si está necesitado, aplíquese otra vez tasa de aplicación para la corrección del pH.



Warning

HAZARD STATEMENT(S)

Causes serious eye irritation.
Causes mild skin irritation.

PRECAUTIONARY STATEMENT(S)

Keep out of reach of children. Read label before use. Wear eye or face protection. Wash hands thoroughly after handling. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If skin irritation occurs: Get medical advice/attention.

Information regarding the contents and levels of metals in this product is available on the internet at <http://www.aapfco.org/metals.htm>

RECOMMENDED SPREADER SETTINGS (Bulk Density: 70)	APPLICATION RATE			
	5 lbs. per 1,000 ft ² (250 kg/ha)		10 lbs. per 1,000 ft ² (500 kg/ha)	
SPREADER TYPE	Setting	Width	Setting	Width
CYCLONE	5 1/2	12	7 1/2	12
EARTHWAY	16	11	26	11
LELY	6 1/2 II	33	10 II	33
LESCO	17 or I	10	24 or M	10
ACCUPRO 2000	15	11	21	12
SCOTTS R8	N	12	T	12
SPYKER 288	5 1/2	12	7 1/2	12
VICON	27	32	40	32
Z-SPRAY	7	16	9	16

**FOR INCORPORATION - AFTER APPLICATION - WET THOROUGHLY
30 MINUTES BEFORE TILLING. WATER IN THOROUGHLY**



MADE IN USA

**AQUA-AID, Inc., 5484 S. Old Carriage Road
Rocky Mount, NC 27803**

800-394-1551 • 252-937-4107 • www.aquaaid.com

Revision date: 1-13-16